


OT 1310
Couplings, Inside/Inside, Conical sealing



DN	Dim.	L	L1 ISO 228/1	L2 ISO 228/1	D	D1	NW	Design pressure Mpa	Weight kg/pce	Article code BSP-threaded EN 1.4404	Article code NPT-threaded EN 1.4404
6	1/8"	32	12	10.0	15.0	15.0	24	10.0	0.06	11-1131-01	11-1131-51
8	1/4"	38	12	13.0	20.5	20.5	30	10.0	0.11	11-1131-02	11-1131-52
10	3/8"	41	14	14.0	24.0	24.0	38	10.0	0.18	11-1131-03	11-1131-53
15	1/2"	46	17	16.0	29.0	29.0	43	10.0	0.24	11-1131-04	11-1131-54
20	3/4"	50	20	18.0	35.0	35.0	50	10.0	0.35	11-1131-05	11-1131-55
25	1"	56	23	22.0	44.0	44.0	60	10.0	0.56	11-1131-06	11-1131-56
32	1 1/4"	62	25	24.0	52.0	52.0	67	6.4	0.69	11-1131-07	11-1131-57
40	1 1/2"	64	26	25.5	58.0	58.0	73	6.4	0.86	11-1131-08	11-1131-58
50	2"	67	28	26.0	71.5	71.5	87	6.4	1.21	11-1131-09	11-1131-59
65	2 1/2"	70	29	28.0	88.0	88.0	110	4.0	1.84	11-1131-10	-
80	3"	75	31	30.0	102.0	102.0	128	4.0	2.62	11-1131-11	-