


OT 1312

Couplings, Outside/Inside, Conical sealing



DN	Dim.	L	L1 ISO 7/1	L2 ISO 228/1	D	d	NW	Design pressure Mpa	Weight kg/pce	Article code BSP-threaded EN 1.4404	Article code NPT-threaded EN 1.4404
6	1/8"	40.5	9	10.0	15.0	5.0	24	10.0	0.07	11-2131-01	11-2131-51
8	1/4"	47.0	12	13.0	20.5	7.5	30	10.0	0.12	11-2131-02	11-2131-52
10	3/8"	53.0	14	14.0	24.0	11.0	38	10.0	0.20	11-2131-03	11-2131-53
15	1/2"	62.0	17	16.0	29.0	14.0	43	10.0	0.29	11-2131-04	11-2131-54
20	3/4"	66.0	18	28.0	35.0	19.0	50	10.0	0.42	11-2131-05	11-2131-55
25	1"	74.0	20	22.0	44.0	24.0	60	10.0	0.67	11-2131-06	11-2131-56
32	1 1/4"	81.0	21	24.0	52.0	31.0	67	6.4	0.90	11-2131-07	11-2131-57
40	1 1/2"	84.0	22	25.5	58.0	38.0	73	6.4	1.09	11-2131-08	11-2131-58
50	2"	87.0	23	26.0	71.5	49.0	87	6.4	1.53	11-2131-09	11-2131-59
65	2 1/2"	97.0	25	28.0	88.0	65.0	110	4.0	2.32	11-2131-10	-
80	3"	109.0	33	30.0	102.0	76.0	125	4.0	3.42	11-2131-11	-