


OT 1311

Couplings, Weld/Weld, Conical sealing



| Dim. | L | T | T1 | D | D1 | NW | Design pressure Mpa | Weight kg/pce | Article code EN 1.4404 |
|-----------|----|-----|-----|------|------|-----|---------------------|---------------|------------------------|
| 14.0/10.0 | 38 | 2.0 | 2.0 | 14.0 | 14.0 | 24 | 10.0 | 0.06 | 11-7131-01 |
| 18.0/14.0 | 40 | 2.0 | 2.0 | 18.0 | 18.0 | 38 | 10.0 | 0.18 | 11-7131-02 |
| 21.3/16.0 | 40 | 2.7 | 2.7 | 21.3 | 21.3 | 38 | 10.0 | 0.18 | 11-7131-03 |
| 25.0/20.0 | 44 | 2.5 | 2.5 | 25.0 | 25.0 | 43 | 10.0 | 0.23 | 11-7131-04 |
| 26.9/23.0 | 44 | 2.0 | 2.0 | 26.9 | 26.9 | 43 | 10.0 | 0.27 | 11-7131-05 |
| 30.0/25.0 | 47 | 2.5 | 2.5 | 30.0 | 30.0 | 50 | 10.0 | 0.34 | 11-7131-06 |
| 33.7/27.2 | 53 | 3.3 | 3.3 | 33.7 | 33.7 | 60 | 10.0 | 0.59 | 11-7131-07 |
| 34.0/30.0 | 53 | 2.0 | 2.0 | 34.0 | 34.0 | 60 | 10.0 | 0.51 | 11-7131-08 |
| 38.0/34.0 | 57 | 2.0 | 2.0 | 38.0 | 38.0 | 60 | 6.4 | 0.48 | 11-7131-09 |
| 42.4/36.0 | 57 | 3.2 | 3.2 | 42.4 | 42.4 | 68 | 6.4 | 0.73 | 11-7131-10 |
| 44.5/40.0 | 57 | 2.3 | 2.3 | 44.5 | 44.5 | 68 | 6.4 | 0.65 | 11-7131-11 |
| 48.3/43.0 | 63 | 2.7 | 2.7 | 48.3 | 48.3 | 74 | 6.4 | 0.87 | 11-7131-12 |
| 51.0/47.0 | 63 | 2.0 | 2.0 | 51.0 | 51.0 | 74 | 6.4 | 0.86 | 11-7131-13 |
| 54.0/50.0 | 69 | 2.0 | 2.0 | 54.0 | 54.0 | 88 | 6.4 | 1.26 | 11-7131-14 |
| 60.3/55.0 | 74 | 2.7 | 2.7 | 60.3 | 60.3 | 88 | 6.4 | 1.21 | 11-7131-15 |
| 77.0/71.0 | 80 | 3.0 | 3.0 | 77.0 | 77.0 | 110 | 6.4 | 1.91 | 11-7131-16 |
| 89.0/81.7 | 83 | 3.7 | 3.7 | 89.0 | 89.0 | 128 | 6.4 | 2.85 | 11-7131-17 |